

美規 UL651認證PVC電線導管

SCH40 適用於90℃電纜配管

單位:mm

規格	外徑及許可差	厚度及許可差	參考重量	長度
			kg/m	
1/2"	21.34±0.10	3.73+0.51	0.248	4m
3/4"	26.67±0.10	2.87+0.51	0.329	4m
1"	33.40±0.13	3.38+0.51	0.483	4m
1 1/4"	42.16±0.13	3.56+0.51	0.653	4m
1 1/2"	48.26±0.15	3.68+0.51	0.779	4m
2"	60.32±0.15	3.91+0.51	1.045	4m
2 1/2"	73.02±0.18	5.16+0.61	1.65	4~6m
3"	88.90±0.20	5.49+0.66	2.16	4~6m
4"	114.30±0.23	6.02+0.71	3.074	4~6m
5"	141.30±0.25	6.55+0.79	4.169	4~6m
6"	168.28±0.28	7.11+0.86	5.414	4~6m

SCH80 適用於90℃電纜配管(可承受高強度外力衝擊)

單位:mm

規格	外徑及許可差	厚度及許可差	參考重量	長度
			kg/m	
1/2"	21.34±0.10	3.73+0.51	0.309	4m
3/4"	26.67±0.10	3.91+0.51	0.419	4m
1"	33.40±0.13	4.55+0.53	0.615	4m
1 1/4"	42.16±0.13	4.85+0.58	0.85	4m
1 1/2"	48.26±0.15	5.08+0.61	1.032	4m
2"	60.32±0.15	5.54+0.66	1.428	4m
2 1/2"	73.02±0.18	7.01+0.84	2.177	4~6m
3"	88.90±0.20	7.62+0.91	2.916	4~6m
4"	114.30±0.23	8.56+1.02	4.264	4~6m
5"	141.30±0.25	9.52+1.14	5.915	4~6m
6"	168.28±0.28	10.97+1.32	8.139	4~6m



南亞塑膠工業股份有限公司
NAN YA PLASTICS CORPORATION