

# HI耐衝擊UPVC塑膠管規格表(一般活套)

標稱管徑		平均外徑	近似內徑	最小厚度	長度	有效長度	每支牌價
HIW, HIB40	1 1/2"	48mm	40mm	3.7mm	4.11m	4m	601.2
HIW, HIB50	2"	60mm	51mm	4.1mm	4.13m	4m	858.6
HIW, HIB65	2 1/2"	76mm	67mm	4.1mm	4.14m	4m	1,103.2
HIW, HIB80	3"	89mm	77mm	5.5mm	4.15m	4m	1,694.2
HIW, HIB100	4"	114mm	100mm	6.6mm	5.165m	5m	3,260.4
HIW125	5"	140mm	125mm	7.0mm	5.18m	5m	4,601.4
HIW, HIB150	6"	165mm	146mm	9.0mm	6.205m	6m	7,694.4
HIW, HIB200	8"	216mm	194mm	10.8mm	6.24m	6m	11,887.9
HIW, HIB250	10"	267mm	239mm	13.3mm	6.285m	6m	18,376.3
HIW, HIB300	12"	318mm	285mm	15.9mm	6.325m	6m	26,287.4
HIW, HIB350	14"	370mm	332mm	18.0mm	6.36m	6m	35,760.7
HIW, HIB400	16"	420mm	376mm	20.5mm	6.385m	6m	46,448.5
HIW, HIB450	18"	470mm	422mm	22.9mm	6.42m	6m	58,448.4
HIW, HIB500	20"	520mm	467mm	25.3mm	6.42m	6m	71,950.0
HIW, HIB600	24"	630mm	566mm	30.7mm	6.55m	6m	106,290.4

"最小厚度"轉載自CNS規範



**南亞塑膠工業股份有限公司**  
NAN YA PLASTICS CORPORATION