

# HI耐衝擊UPVC塑膠管規格表(單放口)

標稱管徑		平均外徑	近似內徑	最小厚度	長度	每支牌價
HIW, HIB13	3/8"	18mm	13mm	2.2mm	4m	122.4
HIW, HIB16	1/2"	22mm	16mm	2.7mm	4m	180.7
HIW, HIB20	3/4"	26mm	20mm	2.7mm	4m	218.2
HIW25	1"	32mm	25mm	3.2mm	4m	316.1
HIW30	1 1/4"	38mm	31mm	3.2mm	4m	382.3
HIW, HIB40	1 1/2"	48mm	40mm	3.7mm	4m	557.3
HIW, HIB50	2"	60mm	51mm	4.1mm	4m	792.0
HIW, HIB65	2 1/2"	76mm	67mm	4.1mm	4m	1,015.2
HIW, HIB80	3"	89mm	77mm	5.5mm	4m	1,555.2
HIW, HIB100	4"	114mm	100mm	6.6mm	5m	3,006.0
HIW125	5"	140mm	125mm	7.5mm	5m	4,230.0
HIW, HIB150	6"	165mm	146mm	9.0mm	6m	7,085.9
HIW, HIB200	8"	216mm	195mm	10.5mm	6m	10,886.4
HIW, HIB250	10"	267mm	241mm	13.0mm	6m	16,707.6
HIW, HIB300	12"	318mm	287mm	15.5mm	6m	23,749.2
HIW, HIB350	14"	370mm	332mm	18.0mm	6m	32,130.0
HIW, HIB400	16"	420mm	376mm	20.5mm	6m	41,569.2
HIW, HIB450	18"	470mm	422mm	22.9mm	6m	52,023.6
HIW, HIB500	20"	520mm	467mm	25.3mm	6m	63,644.4
HIW, HIB600	24"	630mm	566mm	30.7mm	6m	92,728.8

"最小厚度"轉載自CNS規範



**南亞塑膠工業股份有限公司**  
NAN YA PLASTICS CORPORATION