

UPVC 塑膠管規格表 (ASTM SCH40 SCH80 SCH120)

標稱管徑	外徑與平均公差(mm)	長度	厚度與公差(mm)		
			SCH40	SCH80	SCH120
3/8"	17.41±0.10	6m	2.31+0.51	3.20+0.51	---
1/2"	21.34±0.10		2.77+0.51	3.73+0.51	4.32+0.51
3/4"	26.67±0.10		2.87+0.51	3.91+0.51	4.32+0.51
1"	33.40±0.13		3.38+0.51	4.55+0.53	5.08+0.61
1 1/4"	42.16±0.13		3.56+0.51	4.85+0.58	5.46+0.66
1 1/2"	48.26±0.15		3.68+0.51	5.08+0.61	5.72+0.68
2"	60.32±0.15		3.91+0.51	5.54+0.66	6.35+0.76
2 1/2"	73.02±0.18		5.16+0.61	7.01+0.84	7.62+0.91
3"	88.90±0.20		5.49+0.66	7.62+0.91	8.89+1.07
4"	114.30±0.23		6.02+0.71	8.56+1.02	11.10+1.32
5"	141.30±0.25		6.55+0.79	9.52+1.14	12.70+1.52
6"	168.28±0.28		7.11+0.86	10.97+1.32	14.27+1.70
8"	219.08±0.38		8.18+0.99	12.70+1.52	18.24+2.18
10"	273.05±0.38		9.27+1.12	15.06+1.80	21.41+2.56
12"	323.85±0.38		10.31+1.24	17.45+2.08	25.40+3.05
14"	355.60±0.38		11.10+1.35	19.05+2.29	---
16"	406.40±0.48		12.70+1.52	21.41+2.57	---
18"	457.20±0.48		14.27+1.70	23.80+2.84	
20"	508.00±0.58		15.06+1.80	26.19+3.15	
24"	609.60±0.79		17.45+2.08	30.94+3.71	



南亞塑膠工業股份有限公司
NAN YA PLASTICS CORPORATION